



# O' Tannenbaum – Product Specification



M 1:200

## HodgePodge – A variety of study and durable sport and play elements

HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities. Climbing trees, a Wasp's nest, Volleyball nets for sporting activities, cable rides for fun and excitement.

### At a glance.

Product Family:	<b>HodgePodge</b>	Number of Foundations:	<b>1 pc.</b>
Item Number:	<b>95.200.080</b>	Concrete Volume C20/C25:	<b>1.2 m<sup>3</sup></b>
Children's Age:	<b>3+</b>	Number of skilled installers required:	<b>3</b>
Fall Height (DIN EN 1176):	<b>2.00 m (6'-7")</b>	Installation Time without foundation:	<b>6 hours</b>
Length x Width x Height:	<b>2.4 m x 2.4 m x 3.1 m</b> <b>(7'-11" x 7'-11" x 10')</b>	Dimensions of largest part:	<b>Ø 0.1 m x 4.6 m</b> <b>(Ø 0'-1" x 15'-1")</b>
Protective Surfacing Area (DIN EN 1176):	<b>5.4 m x 5.4 m</b>	Weight of heaviest part:	<b>92 kg</b>
Protective Surfacing Area (ASTM 1487):	<b>6.1 m x 6.1 m</b> <b>(19'-9" x 19'-9")</b>	Shipping Volume:	<b>1.7 m<sup>3</sup></b>
Minimum space required DIN EN 1176:	<b>22.5 m<sup>2</sup></b>	Spare part guarantee:	<b>Lifelong</b>
Minimum space required ASTM 1487:	<b>28.4 m<sup>2</sup></b>	Certificate according to EN 1176	<b>No.: Z2.16.01.10256.257</b> <b>TÜV Product Service</b>

### Technical Data.

The following text can also be used for tenders.

#### Central mast:

Steel post 133 mm (5 1/4"), wall thickness 6.3mm (1/4"), anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process.

#### Mast node:

Framework-aluminum ball connector; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; with inlying net tensioning system, secured with a durable EPDM-cap.

#### Rubber membrane:

comprised of durable, vandal-resistant conveyor belt material.

#### Ropes:

U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter Ø 16 mm (5/8").

#### Outer rings:

Bended Framework-steel pipes, Ø 48.3 mm (1 7/8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process.

#### Netting and suspension ropes:

rope crossing points localized by durable, drop forged aluminium-ballknots (no plastic).

  
**Berliner**  
 Berliner Seilfabrik GmbH & Co.  
 Lengeder Straße 2/4  
 D-13407 Berlin

Tel. +49.(0)30.41 47 24-0  
 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com  
 www.berliner-seilfabrik.com



# O' Tannenbaum – Product Specification



**Berliner**  
Berliner Seilfabrik GmbH & Co.  
Lengeder Straße 2/4  
D-13407 Berlin

Tel. +49.(0)30.41 47 24-0  
Fax +49.(0)30.41 47 24-33

[info@berliner-seilfabrik.com](mailto:info@berliner-seilfabrik.com)  
[www.berliner-seilfabrik.com](http://www.berliner-seilfabrik.com)