


# Sculptura.01 – Product Specification



M 1:200

## Terranos Sculptura– Sloping posts in the Terranos® netscape

Sculptura is the “sloping” addition to the otherwise straight Terranos range. A Sculptura element extends with three sloping Terranos posts across the diagonal of a 3 x 3 m (9'-10" x 9'-10") Terranos grid. The centre posts always slope in the opposite direction to the other two outer posts. The diagonal terminates with one straight Terranos post respectively.

### Sculptura.01– At a glance.

Product Family:	<b>Terranos &amp; Terranova</b>	Number of Foundations:	<b>5 pc.</b>
Item Number:	<b>95.180.010</b>	Concrete Volume C20/C25:	<b>2.6 m<sup>3</sup> (91.8 ft<sup>3</sup>)</b>
Children's Age:	<b>5+</b>	Number of skilled installers required:	<b>2</b>
Fall Height (DIN EN 1176):	<b>1.99 m (6'-7")</b>	Installation Time without foundation:	<b>2 hours</b>
Length x Width x Height:	<b>4.5 m x 2.3 m x 2.8 m (14'-8" x 7'-6" x 8'-11")</b>	Dimensions of largest part:	<b>0.1 m x 0.5 m x 4.1 m (0'-4" x 1'-8" x 13'-5")</b>
Protective Surfacing Area (DIN EN 1176):	<b>7.5 m x 5.3 m</b>	Weight of heaviest part:	<b>95 kg (209.4 lbs)</b>
Protective Surfacing Area (ASTM 1487):	<b>6.0 m x 8.2 m (19'-6" x 26'-8")</b>	Shipping Volume:	<b>4.0 m<sup>3</sup> (141.3 ft<sup>3</sup>)</b>
Minimum space required DIN EN 1176:	<b>30.0 m<sup>2</sup></b>	Spare part guarantee:	<b>Lifelong</b>
Minimum space required ASTM 1487:	<b>36.2 m<sup>2</sup> (389.7 sf)</b>	Certificate according to DIN EN 1176:	<b>Z2 16 01 10256 255 TÜV Product Service</b>

## Technical Data.

The following text can also be used for tenders.

### Posts:

Steel pipes Ø 133 mm (5 ¼"); wall thickness 5 - 10 mm (3/16" - 3/8") with a round cast aluminum post top; anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

### Terranos clamps:

Two-part cast aluminum connecting clamps for the height-adjustable connection of rope elements or steel pipes to Terranos steel posts; anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

### Rope:

U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter Ø 16 mm (5/8")

### Nets:

Rope Ø 16mm (5/8"); mesh size minimum 250 x 250 mm (9-4/5"); rope crossing points localized by durable, drop forged aluminum ballknots (no plastic)

  
**Berliner**  
 Berliner Seilfabrik GmbH & Co.  
 Lengeder Straße 2/4  
 D-13407 Berlin

Tel. +49.(0)30.41 47 24-0  
 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com  
 www.berliner-seilfabrik.com

Revision: April 2016

Page 1

