





Product Specification

BerlinerSeilfabrik

Play Equipment Corporation

Product Family	: HodgePodge Games+Sports
Product name	: VIP Swing
Item number	: 97.100.026
Children's age	: 5+
Fall Height	: 10'-8"
Dimensions: length, width, height	: 15'-4" x 6'-7" x 11'-6"
Protective Surfacing Area required	: 28'-9" x 49'-2"
Minimum space required	: 937 Sq.Ft.
Number of foundations	: 2
Concrete Volume C20/25 (3.000 psi)	: 1.4 m ³
Number of skilled installers required	: 2
Installation time without foundation	: 3 hours
Dimensions of largest part	: 5 1/2" x 14'-9"
Weight of heaviest part	: 175 kg
Freight volume	: 0.7 m ³
Gross weight	: 290 kg
Spare part guarantee	: Lifelong
Certificate according to EN 1176	: No.: Z2 05 10 10256 042 – TÜV Product Service



Teetering partner swing with two pendulum seats suspended from rubber-coated chains which are connected to a steel pipe (60.3mm (2 3/8")) with an aluminium ball attached to either end. The steel pipe and seat combination is suspended from ropes which are connected to a steel frame which is constructed from two upright steel posts (133mm (5 1/4")) and one horizontal steel pipe (60.3mm (2 3/8")). Cast aluminium clamps connect the steel posts together. Connections between the ropes and the posts are pivoted.

- Steel posts Jan: Steel pipes \varnothing 133 mm (5 1/4") with rounded cast aluminum post top, minimum wall thickness 7,1mm (1/4"); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process.
- Terranos clamps: Two-part cast aluminum connecting clamps for the height-adjustable connection of rope elements or steel pipes to Terranos steel posts.
- Ropes: U-Rope-round strand ropes with steel cores, \varnothing 16mm (5/8") – unless otherwise noted ; with galvanized wires, external strands covered; with non-abrasive UV-resistant Polyamide-yarn (no Polypropylene!).
- Steel pipe: 1 **Frameworkx**-steel pipe, \varnothing 60.3 mm (2 3/8"); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process.
- Nodes: 2 **Frameworkx**-aluminum ball connectors, \varnothing 250mm (9-13/16"); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process; securely closed with durable ebonite caps.